

	<a href="#">Rapid Floor®</a>	<a href="#">Rapid Floor® Plus</a>	<a href="#">Rapid Floor® Ultra</a>	<a href="#">Commercial Topping®</a>	<a href="#">Rapid Radiant®</a>	<a href="#">Level-Right®</a>	<a href="#">Level-Right® Plus</a>	<a href="#">Level-Right® FS-10</a>
--	------------------------------	-----------------------------------	------------------------------------	-------------------------------------	--------------------------------	------------------------------	-----------------------------------	------------------------------------

**Building Type**

Multifamily	■					■	■	■
Light Commercial		■				■	■	■
Commercial			■	■		■	■	■
Renovation		■	■	■		■	■	■

**Sub-Floor Type**

Wood Panels	■	■	■	■		■		
Old Wood Renovations		■	■	■		■		
Concrete	■	■	■	■		■	■	■
Steel Deck			■	■				
Radiant Heating System					■	■		

■ - Primary Product Selection

■ - Secondary Product Selection; consult your Rapid Floor Systems applicator

This chart is only for reference.

Consult your Rapid Floor Systems applicator for detailed product specifications.

	<a href="#">Rapid Floor®</a>	<a href="#">Rapid Floor® Plus</a>	<a href="#">Rapid Floor® Ultra</a>	<a href="#">Commercial Topping®</a>	<a href="#">Rapid Radiant®</a>	<a href="#">Level-Right®</a>	<a href="#">Level-Right® Plus</a>	<a href="#">Level-Right® FS-10</a>
Wood Panels	3/4" (19 mm)	3/4" (19 mm)	3/4" (19 mm)	3/4" (19 mm)		3/4" (19 mm)	1/2" (12 mm)***	1/2" (12 mm)***
Old Wood Renovations	3/4" (19 mm)	3/4" (19 mm)	3/4" (19 mm)	3/4" (19 mm)		3/4" (19 mm)	3/4" (19 mm)	3/4" (19 mm)
Concrete	1/2" (13 mm)	1/2" (13 mm)	3/8" (10 mm)	3/8" (10 mm)		0-3" (76mm)	3/8"-1 1/2" (10mm - 38mm)	0-3/8" (10mm)
Steel Deck			1" (25 mm)*	1" (25 mm)*		1" (25 mm)**		
Rapid Radiant® System					3/4" (19 mm)**			

\* Thickness over top of flutings

\*\* Thickness over top of heating tubes

\*\*\* 1/2" Thickness can be poured when Laxxon moistop slipsheet and metal lathe or Maxxon MR is used